



Dimensions in mm

Specifications

| | |
|--|---|
| Replaces halogen lamp inside Fresnel fixtures | EGR 750W |
| White Light Options (CCT Kelvin) | Tungsten 3200K, Daylight 5000K |
| Color Temperature Tolerance | +/- 100 K nominal |
| Color Quality | 94 CRI Extended, 95 TLCI |
| Beam Angle | 110° |
| Light Emitting Area | 22 mm (0.88 inches) |
| Weight | 0.33 kg (0.66 lbs) |
| Handling | Metal Enclosure |
| Mounting | Internal Socket: G22 Bi-Post Base |
| Power Supply Range | 90-250V AC 50/60Hz World-Wide Compatible |
| Power Consumption | 100 W MAX |
| Power Connection | Internal Socket: G22 Bi-Post Base |
| AC Dimming | 0-100% continuous on typical triac AC dimmers |
| Ambient Temperature Operation | -20 to 45° C (-4 to 113° F) |
| Storage Temperature | -20 to 70° C (-4 to 158° F) |
| IP Rating | IP 20 |
| Estimated Lifetime of LED | 50,000 hours |
| Estimated Color Shift Over Lifetime (CCT) | +/- 5% |
| Fan noise level: S mode / L mode | 12db / 15db |
| SKUs | VS-EGRD (Daylight), VS-EGRT (Tungsten) |